

Power Driving

7100P



- Short neck (9.5 mm) type
- DIN ISO 2351-2



KT NO.	⊕ No.	Overall length (mm)	g	10 / 150
715000P	PH0	50	8	
715001P	PH1	50	9	
715002P	PH2	50	11	
715003P	PH3	50	11	
715004P	PH4	50	14	10 / 150
716502P	PH2	65	15	
717001P	PH1	70	16	
717002P	PH2	70	17	
717003P	PH3	70	17	
719001P	PH1	90	18	
719002P	PH2	90	20	
719003P	PH3	90	20	
711002P	PH2	100	24	10 / 120
711501P	PH1	150	23	
711502P	PH2	150	33	
711503P	PH3	150	33	

7100H



- DIN ISO 2351-3



KT NO.	mm / inch	Overall length (mm)	g	10 / 150
715002H	H2	50	6	
715025H	H2.5	50	6	
715003H	H3	50	6	
715004H	H4	50	9	
715005H	H5	50	10	
715006H	H6	50	11	
715007H	H7	50	13	
715008H	H8	50	17	
715012SH	3/16	50	20	10 / 150
715014SH	7/32	50	22	
717002H	H2	70	8	
717025H	H2.5	70	8	
717003H	H3	70	9	
717004H	H4	70	13	
717005H	H5	70	15	
717006H	H6	70	18	
717007H	H7	70	21	
717008H	H8	70	25	
711102H	H2	110	11	
711125H	H2.5	110	11	
711103H	H3	110	14	
711104H	H4	110	18	10 / 120
711105H	H5	110	24	
711106H	H6	110	29	
711107H	H7	110	34	
711108H	H8	110	42	
711110H	H10	110	62	8 / 80
711502H	H2	150	16	
711503H	H3	150	18	
711504H	H4	150	25	
711505H	H5	150	34	10 / 120
711506H	H6	150	40	
711507H	H7	150	47	
711508H	H8	150	59	

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, phosphate sunk
- Magnetic **1/4"** Hex size shank driver



order unit : one blister card

7150S



- DIN ISO 2351-1



KT NO.	Tip width (mm)	Tip thickness (mm)	Overall length (mm)	g	10 / 150
715003S1	3.0	0.5	50	6	
715035S1	3.5	0.5	50	6	
715004S2	4.0	0.5	50	7	
715004S1	4.0	0.8	50	7	
715045S1	4.5	0.6	50	7	10 / 150
715005S1	5.0	0.8	50	8	
715055S1	5.5	0.8	50	8	
715006S1	6.0	1.0	50	8	
715065S1	6.5	1.2	50	9	

7100T



- For torx head screw



KT NO.	Size	Overall length (mm)	g	10 / 150
715006T	T6	50	5	
715007T	T7	50	5	
715008T	T8	50	5	
715009T	T9	50	5	
715010T	T10	50	6	
715015T	T15	50	6	
715020T	T20	50	7	
715025T	T25	50	8	
715027T	T27	50	9	
715030T	T30	50	9	
715040T	T40	50	10	
715050T	T50	50	15	10 / 150
717006T	T6	70	7	
717007T	T7	70	7	
717008T	T8	70	7	
717009T	T9	70	7	
717010T	T10	70	8	
717015T	T15	70	8	
717020T	T20	70	10	
717025T	T25	70	11	
717027T	T27	70	14	
717030T	T30	70	14	
717040T	T40	70	15	
711110T	T10	110	14	
711115T	T15	110	14	
711120T	T20	110	18	
711125T	T25	110	19	
711127T	T27	110	24	
711130T	T30	110	24	
711140T	T40	110	28	
711506T	T6	150	16	
711507T	T7	150	16	10 / 120
711508T	T8	150	16	
711509T	T9	150	16	
711510T	T10	150	17	
711515T	T15	150	18	
711520T	T20	150	24	
711525T	T25	150	24	
711527T	T27	150	32	
711530T	T30	150	33	
711540T	T40	150	39	



Power Driving

7100Z



• DIN ISO 2351-2



KT NO.	⊕ No.	Overall length (mm)	g	10 / 150
715001Z	PZ1	50	9	10 / 150
715002Z	PZ2	50	11	
715003Z	PZ3	50	12	
717001Z	PZ1	70	11	
717002Z	PZ2	70	15	10 / 120
717003Z	PZ3	70	15	
719001Z	PZ1	90	13	
719002Z	PZ2	90	19	10 / 120
719003Z	PZ3	90	19	

7100U



• For torx head screw
• Tamper-resistant type



KT NO.	⊕ Size	Overall length (mm)	g	10 / 150
715009U	T9H	50	5	10 / 150
715010U	T10H	50	7	
715015U	T15H	50	7	
715020U	T20H	50	7	
715025U	T25H	50	8	
715027U	T27H	50	9	
715030U	T30H	50	9	
715040U	T40H	50	11	
717010U	T10H	70	8	
717015U	T15H	70	8	
717020U	T20H	70	10	10 / 120
717025U	T25H	70	11	
717027U	T27H	70	13	
717030U	T30H	70	13	
717040U	T40H	70	15	
711110U	T10H	110	14	
711115U	T15H	110	14	
711120U	T20H	110	18	
711125U	T25H	110	19	
711127U	T27H	110	24	
711130U	T30H	110	24	
711140U	T40H	110	28	

7100R



KT NO.	⊕ Size	Overall length (mm)	g	10 / 150
715000R	RB0	50	7	10 / 150
715001R	RB1	50	8	
715002R	RB2	50	8	
715003R	RB3	50	8	
717000R	RB0	70	9	
717001R	RB1	70	11	
717002R	RB2	70	13	
717003R	RB3	70	13	

2128PR



• torx head tamper-resistant & L-type holder set



8 PC.

Contents 0.17 10 / 60

	7170U	T10H, T15H, T20H, T25H, T27H, T30H, T40H
	158902ERA	

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, phosphate sunk
- Magnetic **1/4"** Hex size shank driver



order unit: one blister card

2138PR



• Hexagon head power bits & L-type holder set



8 PC.

Contents 0.24 10 / 60

	7150H	H2, H3, H4, H5, H6, H7, H8
	158902ERA	

7400P



• Short head type



KT NO.	⊕ No.	Overall length (mm)	g	10 / 150
745002P	PH2	50	11	10 / 150
747501P	PH1	75	16	10 / 150
747502P	PH2	75	15	10 / 150
747503P	PH3	75	16	10 / 150
741002P	PH2	100	23	10 / 120
741502P	PH2	150	37	10 / 100
742002P	PH2	200	50	10 / 100
743002P	PH2	300	70	10 / 40
743003P	PH3	300	77	10 / 40

7300P



• Long head type



KT NO.	⊕ No.	Overall length (mm)	g	10 / 150
734501P	PH1	45	9	10 / 150
734502P	PH2	45	9	
734503P	PH3	45	10	
736501P	PH1	65	14	
736502P	PH2	65	14	10 / 120
736503P	PH3	65	14	
731101P	PH1	110	26	
731102P	PH2	110	26	
731103P	PH3	110	26	10 / 120
731502P	PH2	150	32	
731503P	PH3	150	33	



5mm Hex size shank driver order unit: one box

Insert Size: The suggested size is according to the depth of bit holder which a bit is inserted.

7200P



• Long head typed



KT NO.	⊕ No.	Overall length (mm)	g	10 / 100
726502P	PH2	65	8	10 / 100
727502P	PH2	75	10	
721102P	PH2	110	14	

Power Driving

7100P-S1

- Short neck (9.5 mm) type
- DIN ISO 2351-2



KT NO.	No.	Overall length (mm)	g	set / box
715000P-S1	PH0	50	16	1 / 20
715001P-S1	PH1	50	18	
715002P-S1	PH2	50	22	
715003P-S1	PH3	50	22	
715004P-S1	PH4	50	28	
716502P-S1	PH2	65	30	
717001P-S1	PH1	70	32	
717002P-S1	PH2	70	34	
717003P-S1	PH3	70	34	
719001P-S1	PH1	90	36	
719002P-S1	PH2	90	40	
719003P-S1	PH3	90	40	
711002P-S1	PH2	100	48	
711501P-S1	PH1	150	46	
711502P-S1	PH2	150	66	
711503P-S1	PH3	150	66	

7100H-S1

- DIN ISO 2351-3



KT NO.	mm / inch	Overall length (mm)	g	set / box
715002H-S1	H2	50	12	1 / 20
715025H-S1	H2.5	50	12	
715003H-S1	H3	50	12	
715004H-S1	H4	50	18	
715005H-S1	H5	50	20	
715006H-S1	H6	50	22	
715007H-S1	H7	50	26	
715008H-S1	H8	50	34	
715012SH-S1	3/16	50	20	
715014SH-S1	7/32	50	22	
717005H-S1	H5	70	30	
717006H-S1	H6	70	36	
711102H-S1	H2	110	22	
711125H-S1	H2.5	110	22	
711103H-S1	H3	110	28	
711104H-S1	H4	110	36	
711105H-S1	H5	110	48	
711106H-S1	H6	110	58	
711107H-S1	H7	110	68	
711505H-S1	H5	150	68	
711507H-S1	H7	150	94	
711512SH-S1	3/16	150	68	

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, phosphate sunk
- Magnetic
- 2 PC. bits set **1/4" Hex size shank driver** order unit : one blister card



7150S-S1

- DIN ISO 2351-1



KT NO.	Tip width (mm)	Tip thickness (mm)	Overall length (mm)	g	set / box
715003S1-S1	3.0	0.5	50	12	1 / 20
715035S1-S1	3.5	0.5	50	12	
715004S2-S1	4.0	0.5	50	14	
715004S1-S1	4.0	0.8	50	14	
715045S1-S1	4.5	0.6	50	14	
715005S1-S1	5.0	0.8	50	16	
715055S1-S1	5.5	0.8	50	16	
715006S1-S1	6.0	1.0	50	16	
715065S1-S1	6.5	1.2	50	18	

7100T-S1

- For torx head screw



KT NO.	Size	Overall length (mm)	g	set / box
715006T-S1	T6	50	10	1 / 20
715007T-S1	T7	50	10	
715008T-S1	T8	50	10	
715009T-S1	T9	50	10	
715010T-S1	T10	50	12	
715015T-S1	T15	50	12	
715020T-S1	T20	50	14	
715025T-S1	T25	50	16	
715027T-S1	T27	50	18	
715030T-S1	T30	50	18	
715040T-S1	T40	50	20	
715050T-S1	T50	50	30	
717006T-S1	T6	70	14	
717007T-S1	T7	70	14	
717008T-S1	T8	70	14	
717009T-S1	T9	70	14	
717010T-S1	T10	70	14	
717015T-S1	T15	70	16	
717020T-S1	T20	70	16	
717025T-S1	T25	70	20	
717027T-S1	T27	70	22	
717030T-S1	T30	70	28	
717040T-S1	T40	70	28	
711110T-S1	T10	110	30	
711115T-S1	T15	110	28	
711120T-S1	T20	110	28	
711125T-S1	T25	110	36	
711127T-S1	T27	110	38	
711130T-S1	T30	110	48	
711140T-S1	T40	110	48	
711506T-S1	T6	150	56	
711507T-S1	T7	150	32	
711508T-S1	T8	150	32	
711509T-S1	T9	150	32	
711510T-S1	T10	150	34	
711515T-S1	T15	150	36	
711520T-S1	T20	150	48	
711525T-S1	T25	150	48	
711527T-S1	T27	150	64	
711530T-S1	T30	150	66	
711540T-S1	T40	150	78	

